



Principal Dimensions(mm)			Designation	Basic Load Ratings(kN)		Limited Speed(rpm)	
d	D	B		Cr	Cor	Grease	Oil
25	47	12	7005ACTA	11.1	7	12000	17000
25	52	15	7205ACTA	15.8	9.7	11000	16000
30	55	13	7006ACTA	14.4	9.8	9500	14000
30	62	16	7206ACTA	22.1	13.5	9000	13000
35	62	14	7007ACTA	17.3	12.1	8500	12000
35	72	17	7207ACTA	29.2	18	8000	11000
40	68	15	7008ACTA	18.7	14.1	8000	11000
40	80	18	7208ACTA	36.8	25.4	7500	10000
45	75	16	7009ACTA	24.7	19.1	7500	10000
45	85	19	7209ACTA	38.6	28.1	6700	9000
50	80	16	7010ACTA	25.3	20.5	6700	9000
50	90	20	7210ACTA	40.8	30.1	6300	8500
55	90	18	7011ACTA	35.5	26.5	6000	8000
55	100	21	7211ACTA	50.8	38.2	5600	7000
60	95	18	7012ACTA	37	31.3	5600	7500
60	110	22	7212ACTA	58.1	46	5300	7000
65	100	18	7013ACTA	38	33.6	5300	7000
65	120	23	7213ACTA	66.6	52.1	4800	6300
70	110	20	7014ACTA	45.8	40.9	5000	6700
70	125	24	7214ACTA	69.4	57	4500	5800
75	115	20	7015ACTA	47.5	43.3	4800	6300
75	130	25	7215ACTA	75.3	62.8	4300	5600

ACTN Series

80	125	22	7016ACTA	57.5	51	4500	6000
80	140	26	7216ACTA	91.3	65.1	4000	5300
85	130	22	7017ACTA	55	52.8	4300	5600
85	150	28	7217ACTA	94.9	80.8	3800	5000
90	140	24	7018ACTA	65	62.8	4000	5300
90	160	30	7218ACTA	122	106.5	3600	4800
95	145	24	7019ACTA	69.8	69.1	3800	5000
95	170	32	7219ACTA	128.4	107.8	3400	4500
100	150	24	7020ACTA	69	69.7	3800	5000
100	180	34	7220ACTA	142.3	120.6	3200	4300
105	160	26	7021ACTA	80.9	72.2	3600	4800
105	190	36	7221ACTA	159	135.1	3000	4000
110	170	28	7022ACTA	98.5	93.9	3400	4600
110	200	38	7222ACTA	176.3	151.2	2800	3800
120	180	28	7024ACTA	103.5	104.5	2800	3800
130	200	33	7026ACTA	122.4	127.8	2600	3400